

Performance

Measuring range	0.1 to 0.5 ppm	0.5 to 8 ppm	8 to 16 ppm	
Number of pump strokes	2 to 5(200 to 500 ml)	1(100 ml)	1/2(50 ml)	
Correction factor	1/2 to 1/5	1	2	
Sampling time	2 to 5 min	1 min	30 sec	

Detecting limit:

0.05 ppm (5 pump strokes)

Colour change:

White → Pale pink

Corrections for temperature & humidity: Unnecessary Relative standard deviation: 10 % (for 0.5

10 % (for 0.5 to 2 ppm), 5 % (for 2 to 8 ppm)

Shelf life:

3 years

Reaction principle

Chlorine reacts with reagent to produce pale pink stain.

Possible coexisting substances and their interferences (NOTE: Page 2-5)

Substance	Concentration	Interference	Changes colour by itself to
Nitric oxide		+	Pale pink
Ozone		+	Pale pink
Nitrogen dioxide		+	Pale pink
Chlorine dioxide		+	Pale pink
Bromine, lodine		+	Pale pink

Other substances measurable with this detector tube

Substance	Correction	No. of pump strokes	Measuring range
Bromine	Factor: 0.1	4	0.05 to 0.8 ppm
Chlorine dioxide	Factor: 0.6	1	0.3 to 4.8 ppm

Calibration gas generation

Permeation tube method